

MOBILE **CONTAINING**

DFE DISPENSER



DESIGN

FUNCTION

ENERGY SAVING

FOR THE FUTURE

•

FOR THE USER

•

FOR THE ENVIRONMENT

Description of DFE dispenser

Available for plates, trays, baskets and direct stacking

All DFE dispensers incorporate the following features

- Mobile with 4 swivel castors, each 125 mm (5"), 2 with brake.
- Generally finished in 18/10 stainless steel, with 320 grain.
- Smooth 35 mm radius to upper corners of side panels.
- End panels can be customised to match the decor of the foodservice area.
- Pushbar ergonomically located.
- Fitted with 4 broad corner buffers.
- Each stacking unit can be individually adjusted by a multi-spring system.
- Each plate stacking unit can be provided with a cover, with a simple locking mechanism.

All heated DFE dispensers incorporate the following features:

- Control panel conveniently located, including on/off switch, green mains-on neon protected by moisture cap and individual thermostat to each stacking unit.
- Ergonomically located spiral cable in Neopren 3 x 1 mm², fitted with 13amp plug, with plug holder.
- Spiral cable is fitted to opposite end of dispenser to the control panel and push bar, to facilitate operation when DFE dispenser is positioned in a service counter.
- Each stacking unit is individually heated by an electric element rated at 700 W - 230 V located directly under the stacking unit.
- DFE heated units for baskets and direct stacking have 2 elements 700 W each in one compartment.
- Stacking units are individually controlled and insulated, with a temperature range 30 - 120 °C, ie unit A at ambient temperature and unit B at 80 °C.

Options available:

- Round polycarbonate cover in dark grey.
- Round polycarbonate insulated cover in darkgrey.
- Square stainless steel cover.
- Stainless steel castors.

Dealer

- MOBILE UK LIMITED
- Rookwood House
- 1, Rookwood Drive
- Rochdale OL11 3PE

- Phone: 01706 - 868160
- Fax: 01706 - 868160