



**New Concept DFR incounter plate dispenser comprising unheated dispenser mechanism which may be mounted directly in a counter top for an ambient application or mounted in a heated outer casing for heated applications. The dispenser mechanism is easily removable from the counter or heated casing for cleaning and maintenance.**

General specification DFR incounter plate dispenser.

With four fixed guides.

Circular flange with 'flat' guide tops.

Capacity of approximately 60 round plates, stacking height of 620 mm.

Multispring mechanism to give easy adjustment for different plate weights.

Stacking unit with 8 heat resistant Teflon rollers.

Five different models, for round plates 160 - 338 mm.

DFR outer casing with heating element of 400W, located in base.

Controlled by remote control panel incorporating adjustable min/max thermostat and on/off switch with pilot light.

Generally finished in stainless steel.

Operates from 230V - 50HZ - 1PH electric supply.

00.1123.NC	DFR 210 unheated for plates 170-208 mm	02.1513.NC	DFR 210 heated for plates 170-208 mm
00.1133.NC	DFR 240 unheated for plates 200-238 mm	02.1523.NC	DFR 240 heated for plates 200-238 mm
00.1143.NC	DFR 280 unheated for plates 240-278 mm	02.1533.NC	DFR 280 heated for plates 240-278 mm
00.1153.NC	DFR 310 unheated for plates 270-308 mm	02.1543.NC	DFR 310 heated for plates 270-308 mm
00.1163.NC	DFR 340 unheated for plates 300-338 mm	02.1563.NC	DFR 340 heated for plates 300-338 mm